

Revision Date: 13-Dec-2024

Revision Number: 6

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

INSL-X CABINET COAT URETHANE ACRYLIC SATIN TRIM & CABINET ENAMEL BASE 4

CC654BF UF654B Water thinned paint All Paint No information available

Manufactured For

Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.inslx.ca

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.insl-x.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1

Label elements

Warning

Hazard statements Causes serious eye irritation May cause an allergic skin reaction



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves/clothing and eye/face protection

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention **Skin** IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

May cause allergic skin reaction

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Acrylic polymer	-	10 - 30%	-	-
Kaolin	1332-58-7	7 - 13%	-	-
1,4-Cyclohexanedimethanol	105-08-8	1 - 5%	-	-
Ammonia	7664-41-7	0.5 - 1%	-	-
Hexanedioic acid, dihydrazide	1071-93-8	0.5 - 1%	-	-

Ammonium hydroxide	1336-21-6	0.1 - 0.25%	-	-		
*The exact percentage (concer	·		as a trade secret			
	4. FIRST AID MEASURES					
General Advice	No hazards wh	No hazards which require special first aid measures.				
Eye Contact			Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.			
Skin Contact			diately with soap and ontaminated clothes ar			
Inhalation		Move to fresh	air. If symptoms persis	t, call a physician.		
Ingestion Clean mouth with water and afterwards drink plent water. Consult a physician if necessary.						
Most Important Symptoms/E	May cause alle	ergic skin reaction.				
Notes To Physician		Treat symptom	atically.			
5. FIRE-FIGHTING MEASURES						
	5. FIRE-FIG	HTING MEASU	JRES			
Suitable Extinguishing Media		Use extinguish	JRES ing measures that are and the surrounding e			
Suitable Extinguishing Media Protective equipment and pro	a	Use extinguish circumstances ers As in any fire,	ing measures that are and the surrounding e wear self-contained br and, MSHA/NIOSH (ap	environment. eathing apparatus		
	a ecautions for firefight	Use extinguish circumstances ers As in any fire, pressure-dema and full protect	ing measures that are and the surrounding e wear self-contained br and, MSHA/NIOSH (ap	environment. eathing apparatus oproved or equivalent)		
Protective equipment and protective equipment and protection of the second seco	a ecautions for firefight om The Chemical	Use extinguish circumstances eers As in any fire, pressure-dema and full protect Closed contair	ing measures that are and the surrounding e wear self-contained br and, MSHA/NIOSH (ap ive gear.	environment. eathing apparatus oproved or equivalent)		
Protective equipment and prospecific Hazards Arising Fro	a ecautions for firefight om The Chemical pact	Use extinguish circumstances ers As in any fire, pressure-dema and full protect Closed contain extreme heat.	ing measures that are and the surrounding e wear self-contained br and, MSHA/NIOSH (ap ive gear.	environment. eathing apparatus oproved or equivalent)		
Protective equipment and prospecific Hazards Arising Fro	a ecautions for firefight om The Chemical pact	Use extinguish circumstances eers As in any fire, pressure-dema and full protect Closed contain extreme heat. No	ing measures that are and the surrounding e wear self-contained br and, MSHA/NIOSH (ap ive gear.	environment. eathing apparatus oproved or equivalent)		
Protective equipment and pro Specific Hazards Arising Fro Sensitivity to mechanical imp Sensitivity to static discharg Flash Point Data Flash point (°F) Flash Point (°C)	a ecautions for firefight om The Chemical pact	Use extinguish circumstances ers As in any fire, pressure-dema and full protect Closed contain extreme heat. No No No Not Applicable Not applicable	ing measures that are and the surrounding e wear self-contained br and, MSHA/NIOSH (ap ive gear.	environment. eathing apparatus oproved or equivalent)		

NFPA

Health hazards
Flammability
Stability
Special:

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

1

0 0

Not Applicable

adequate ventilation.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Other Information

Environmental precautions

Methods for Cleaning Up

See Section 12 for additional Ecological Information.

Avoid contact with skin, eyes and clothing. Ensure

Prevent further leakage or spillage if safe to do so.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Storage

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of children.

Incompatible Materials

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Kaolin	TWA: 2 mg/m ³	2 mg/m³ - TWA	2 mg/m ³ - TWA	2 mg/m³ - TWA	5 mg/m ³ - TWAEV
	particulate matter				
	containing no asbestos				
	and <1% crystalline				
	silica, respirable				
	particulate matter				

Ammonia	STEL: 35 ppm TWA: 25 ppm	25 ppm - TWA 17 mg/m ³ - TWA 35 ppm - STEL 24 mg/m ³ - STEL	25 ppm - TWA 35 ppm - STEL	25 ppm - TWA 35 ppm - STEL	25 ppm - TWAEV 17 mg/m ³ - TWAEV 35 ppm - STEV 24 mg/m ³ - STEV
Ammonium hydroxide	STEL: 35 ppm TWA: 25 ppm	-	-	-	-

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Hygiene Measures

Engineering Measures

Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold Density (lbs./gal) Specific Gravity pH Viscosity (cps) Solubility(ies) Water solubility Evaporation Rate Vapor pressure @20 °C (kPa) Relative vapor density Wt. % Solids Vol. % Solids Vol. % Solids Wt. % Volatiles VoC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing point (°F)	liquid little or no odor No information available 9.1 - 9.5 1.09 - 1.14 No information available No information available No information available No information available No information available No information available No information available 40 - 50 35 - 45 50 - 60 55 - 65 < 50 212 100 32
Boiling Point (°C)	100
Freezing point (°F) Freezing Point (°C)	32 0
Flash point (°F)	Not Applicable
Flash Point (°C) Method	Not applicable
Flammability (solid, gas)	Not applicable Not applicable

Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°F) Decomposition Temperature (°C) Partition coefficient Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable	
Chemical Stability	Stable under normal conditions.	
Conditions to avoid	Prevent from freezing.	
Incompatible Materials	No materials to be especially mentione	
Hazardous Decomposition Products	None under normal use.	
Possibility of hazardous reactions	None under normal conditions of use.	

11. TOXICOLOGICAL INFORMATION

Product Information Information on likely routes of exposure

Principal Routes of Exposure

Acute Toxicity Product Information Eye contact, skin contact and inhalation.

No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.

Target organ effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	36895 mg/kg
ATEmix (inhalation-dust/mist)	76.1 mg/l

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
1,4-Cyclohexanedimethanol 105-08-8	= 3200 mg/kg (Rat)	-	-
Ammonia 7664-41-7	= 350 mg/kg (Rat)	-	= 9850 mg/m³ (Rat)1 h = 13770 mg/m³ (Rat)1 h
Ammonium hydroxide 1336-21-6	= 350 mg/kg (Rat)	-	-

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

Not applicable

Component Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

TDG	Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical name	CAS No.	Weight-%	NPRI Parts 1- 4
Ammonia	7664-41-7	0.5 - 1%	Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

16. OTHER INFORMATION					
HMIS Health hazards Flammability Reactivity: Personal protection	1 0 0 -				
HMIS Legend 0 - Minimal Hazard 1 - Slight Hazard 2 - Moderate Hazard 3 - Serious Hazard 4 - Severe Hazard * - Chronic Hazard					

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554	
Revision Date:	13-Dec-2024	
Reason for revision	Not available	

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet